

X-S3000 PRO FOG MACHINE SPECIFICATIONS

X-S3000 is a professional fog machine with fog output up to 40000cuft/min. For easier operation it designed with a rotary output control button to adjust the smoke output volume. X-S3000 can continuously generate fog in low output mode, with 40s output in 100% output status.

Features

- Rotary output control button, easier smoke amount adjustment;
- Super long effect time, max output up to 40s, continuously in low output mode;
- Optimized atomizer with high precision circuit, ensure more uniform smoke effect;
- NEUTRIK® POWERCON and DMX socket with quality assurance;
- Both 3-pin and 5-pin DMX socket available.
- Build-in LCD screen, user friendly.

Specifications

Dimension

660 x 404 x 290 mm

Weight

16.6 kg

Input

200-240VAC, 50/60 Hz
100 -120VAC, 50/60 Hz

Work Power

3000W (220V version)
2000W (110V version)

Heat-up Time

220V version: 7min
110V version: 12min

Max Continuous Output Duration

Max output: 40s
Low output: continuously

Fog Output

40000cuft/min

Tank Capacity

9L

DMX Channels

1 channel

Fluid Consumption Rate

5min/L



CONSUMABLES FOR X-S3000

- FX-M: medium fog fluid
- FX-BM: medium fog fluid, suggest to use in the bar or club etc.
- Package: 3L/bottle, 4bottles/carton.
- Fog fluid Consumption: 5min/L.



EFFECTS

